

**IN THE CLAIMS:**

Please consider all claims 1-44 cancelled as per previous response dated 22<sup>nd</sup> July 2009 without prejudice or disclaimer.

Please cancel claims 45-85 without prejudice or disclaimer.

Please add all new claims 86-111.

86. (New) An **impact driver** for driving an **elongate object** into a **body** in any plane from the horizontal to the vertical, said **impact driver** comprising
- a) **chassis**,
  - b) a **ram** supported by said **chassis** in a manner allowing rectilinear movement of said **ram** relative to said **chassis**,
  - c) a **linear induction motor** including
    - (i) a **stator** mounted to said **chassis**, and
    - (ii) a **linear induction motor reaction member** composed of at least one plat of an electrically conductive material mounted to said **ram**,
    - (iii) the **stator** being positioned to operatively interact with **linear induction motor reaction member** to accelerate the **reaction member** substantially along a length of movement of the **reaction member** to move the **reaction member**
      - from a **retracted position** to an **impact position**, and
      - from the **impact position** to the **retracted position**,
  - d) whereby, when the said **reaction member** is accelerated to move from said **retracted position** to said **impact position**, the **ram** is accelerated at an increasing rate throughout its movement by the **reaction member** to substantially increase its kinetic energy for causing an impact force to be imparted on said **elongate object** in the elongate direction thereof.
87. (New) The **impact driver** as claimed in claim 86, wherein said **ram** includes an **impact head** for receiving said **impact force** from the **ram** and transmitting it to an **elongate object**.
88. (New) The **impact driver** as claimed in claim 87, wherein said **ram** includes an elongate ram support structure, said **ram support structure** having a first and second ends, and wherein said **impact head** is provided at a first end of said **ram support structure**.
89. (New) The **impact driver** as claimed in claim 88, wherein said **reaction member** is of an elongate configuration, and is secured to the **ram support structure** to extend in the elongate direction of said **ram support structure** between said first and second ends thereof.

90. (New) The **impact driver** as claimed in claim 87, wherein said **impact head** is of a robust and substantially solid material suitable for the transferal of an impact from the **ram** to the **elongate object**.
91. (New) The **impact driver** as claimed in claim 86, wherein said **chassis** provides **bearings** which locate and support said **ram** for rectilinear movement within said **chassis**.
92. (New) The **impact driver** as claimed in claim 91, wherein said **bearings** are located within a **casing** of said **chassis**, said **ram** also at least in part provided and retained by said **bearings** within said **casing** of said **chassis**.
93. (New) The **impact driver** as claimed in claim 91, wherein said **stator** of said **linear induction motor** is positioned within the **casing** of said **chassis**.
94. (New) The **impact driver** as claimed in claim 86, wherein said **chassis** includes a **casing** defining an elongate chamber within which at least part of said **ram** is able to move in the elongate direction.
95. (New) The **impact driver** as claimed in claim 86, wherein the relative position of said **ram** at least when in one position with respect to said **chassis** is able to be sensed by an **electronic sensor**.
96. (New) The **impact driver** as claimed in claim 95, wherein said **electronic sensor** is a limit sensor for detecting the reaching of the **ram** to or proximate to its **retracted position**.
97. (New) The **impact driver** as claimed in claim 95, wherein said **electronic sensor** is in communication with a controller for controlling of the **linear induction motor**, in order for the **electronic sensor** to actuate the controller to accelerate the said **ram** from the **retracted position** to the **impact position**.
98. (New) The **impact driver** as claimed in claim 86, wherein said **stator** is controlled to accelerate the **ram** from the **retracted position** to the **impact position** at a rate different and most usually greater than from the **impact position** to the **retracted position**.
99. (New) The **impact driver** as claimed in claim 86, wherein an **anvil assembly** is positioned relative to said **chassis** to hold an **anvil** in alignment to the rectilinear direction of movement of said **ram** to be interposed between the head of said **elongate object** and said **impact head** for the purpose of providing a cushioning to the impact force of said **ram** applied to said **elongate object**.
100. (New) The **impact driver** as claimed in claim 99, wherein said **anvil assembly** is in a translatable engagement with said **chassis**.

101. (New) The **impact driver** as claimed in claim 99, wherein said **anvil assembly** presents said **anvil** at a location remote from said **chassis**.
102. (New) The **impact driver** as claimed in claim 86, wherein said **chassis** is mounted to a **support structure**.
103. (New) The **impact driver** as claimed in claim 99, wherein said **chassis** is mounted to a **support structure** and said **anvil assembly** is in a translatable engagement with said **support structure** to permit its movement relative thereto and parallel to the rectilinear direction of movement.
104. (New) The **impact driver** as claimed in claim 86, wherein said **support structure** includes a **mounting arrangement** for mounting the **chassis** to a **vehicle**.
105. (New) The **impact driver** as claimed in claim 104, wherein said **mounting arrangement** allows said **support structure** to rotate relative to said **vehicle**.
106. (New) The **impact driver** as claimed in claim 104, wherein said **mounting arrangement** allows said **support structure** to translate relative to said **vehicle**.
107. (New) The **impact driver** as claimed in claim 86, wherein said **chassis** is mounted to a **support device** selected from one of a vehicle, a vessel and a derrick.
108. (New) The **impact driver** as claimed in claim 107, wherein said **chassis** is connected to the **support device** by an articulated mounting arrangement configured for mounting the **chassis** to the **support device** in an articulated manner.
109. (New) The **impact driver** as claimed in claim 86, wherein the **impact driver** is a pile driver.
110. (New) The **impact driver** as claimed in claim 86, wherein when said **reaction member** is accelerated to move from said **retracted position** to said **impact position**, the acceleration of the said **ram** is enhanced by the addition of a gravitational force component that increases from zero in the horizontal plane to a maximum additional acceleration of  $9.81\text{m/s}^2$  in the vertical plane.
111. (New) The **impact driver** as claimed in claim 86, wherein said **elongate object** can be extracted from said **body** by nature of the following arrangement:
  - a) said **impact position** and said **retracted position** are reversed with respect to said **elongate object** so that the said **ram** is accelerated away from said **elongate object**,
  - b) said **ram** includes an engagement arrangement for engaging with said **elongate object** to transmit forces from the **linear induction motor** to the **elongate object**, thereby to extract the **elongate object**; and
  - c) the movement of said **ram** being controllable through said **linear induction motor** to reduce said **ram's** impact on said **elongate object** to a

lesser extent when said **ram** returns to a more proximate position to said **elongate object** between extraction strokes.